



# SAFETY DATA SHEET

## 1. Identification

**Product number** 1000001319  
**Product identifier** **15 OZ TERAND GRAFFITI RMVR PLSTC-SAFE**  
**Company information** CPC  
1005 S. Westgate Drive  
Addison, IL 60101 United States  
**Company phone** General Assistance 630-543-7600  
**Emergency telephone US** 1-866-836-8855  
**Emergency telephone outside US** 1-952-852-4646  
**Version #** 01  
**Supersedes date** 06-23-2014  
**Recommended use** CLEANER  
**Recommended restrictions** None known.

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable aerosols	Category 1
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Reproductive toxicity	Category 1A
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
<b>OSHA defined hazards</b>	Not classified.	

### Label elements



**Signal word** Danger

**Hazard statement** Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

**Precautionary statement**

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

**Response** If swallowed: Immediately call a poison center/doctor. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

<b>Storage</b>	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
<b>Supplemental information</b>	32.14% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 32.14% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Toluene		108-88-3	20 - 40
Propane		74-98-6	10 - 20
2-Butoxyethanol		111-76-2	2.5 - 10
Acetone		67-64-1	2.5 - 10
Butane		106-97-8	2.5 - 10
Diethylene Glycol Monobutyl Ether		112-34-5	2.5 - 10
9-Octadecenoic Acid		112-80-1	1 - 2.5
Sodium Hydroxide		1310-73-2	0.1 - 1
Other components below reportable levels			20 - 40

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Skin contact</b>	Remove contaminated clothing. Wash off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.
<b>Most important symptoms/effects, acute and delayed</b>	Irritation of eyes and mucous membranes. Prolonged exposure may cause chronic effects. May cause drowsiness or dizziness.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Powder. Water. Foam. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	None known.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire-fighting equipment/instructions</b>	Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

**General fire hazards** Extremely flammable aerosol.

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up** Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

**Environmental precautions** Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

**Precautions for safe handling** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Ground and bond containers when transferring material. Do not re-use empty containers. Do not breathe gas. Do not get this material in contact with skin. Avoid contact with eyes. Avoid contact during pregnancy/while nursing. Avoid prolonged exposure. Use only in well-ventilated areas. Use personal protective equipment as required. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Do not empty into drains.

**Conditions for safe storage, including any incompatibilities** Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Level 2 Aerosol.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3
Acetone (CAS 67-64-1)	PEL	50 ppm 2400 mg/m3
Propane (CAS 74-98-6)	PEL	1000 ppm 1800 mg/m3
Sodium Hydroxide (CAS 1310-73-2)	PEL	1000 ppm 2 mg/m3

#### US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm	
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
Butane (CAS 106-97-8)	STEL	1000 ppm	Inhalable fraction and vapor.
Diethylene Glycol	TWA	10 ppm	
Monobutyl Ether (CAS 112-34-5)			
Sodium Hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m <sup>3</sup>	
Toluene (CAS 108-88-3)	TWA	20 ppm	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m <sup>3</sup>
		5 ppm
Acetone (CAS 67-64-1)	TWA	590 mg/m <sup>3</sup>
		250 ppm
Butane (CAS 106-97-8)	TWA	1900 mg/m <sup>3</sup>
		800 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m <sup>3</sup>
		1000 ppm
Sodium Hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m <sup>3</sup>
Toluene (CAS 108-88-3)	STEL	560 mg/m <sup>3</sup>
		150 ppm
	TWA	375 mg/m <sup>3</sup>
		100 ppm

**Biological limit values****ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

\* - For sampling details, please see the source document.

**Exposure guidelines****US - California OELs: Skin designation**

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies**

2-Butoxyethanol (CAS 111-76-2)

Skin designation applies.

Toluene (CAS 108-88-3)

Skin designation applies.

**US - Tennessee OELs: Skin designation**

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

**US NIOSH Pocket Guide to Chemical Hazards: Skin designation**

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear eye/face protection. Wear safety glasses with side shields (or goggles).

**Hand protection**

Wear protective gloves.

<b>Skin protection</b>	
<b>Other</b>	Wear appropriate chemical resistant clothing.
<b>Respiratory protection</b>	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>General hygiene considerations</b>	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

<b>Appearance</b>	Viscous. Liquid.
<b>Physical state</b>	Liquid.
<b>Form</b>	Aerosol.
<b>Color</b>	Tan.
<b>Odor</b>	Solvent.
<b>Odor threshold</b>	Not available.
<b>pH</b>	12.5 - 13.4 estimated
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	193.64 °F (89.8 °C) estimated
<b>Flash point</b>	-156.0 °F (-104.4 °C) Propellant estimated
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	1.9 % estimated
<b>Flammability limit - upper (%)</b>	9.5 % estimated
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	60 - 75 psig @70F estimated
<b>Vapor density</b>	Not available.
<b>Relative density</b>	0.74 g/cm3 estimated
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Density</b>	0.74 g/cm3 estimated
<b>Flammability class</b>	Flammable IB estimated
<b>Heat of combustion</b>	20.95 kJ/g estimated
<b>Heat of combustion (NFPA 30B)</b>	20.95 kJ/g estimated
<b>Percent volatile</b>	95.33 % estimated
<b>Specific gravity</b>	0.74 estimated
<b>VOC (Weight %)</b>	47.76 % estimated

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
-------------------	---

<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Avoid temperatures exceeding the flash point. Reacts violently with strong acids. This product may react with oxidizing agents. Do not mix with other chemicals.
<b>Incompatible materials</b>	Strong oxidizing agents. Oxidizing agents. Acids. Fluorine. Chlorine. Nitrates.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Ingestion</b>	May be fatal if swallowed and enters airways.
<b>Inhalation</b>	May be fatal if swallowed and enters airways. Prolonged inhalation may be harmful. Narcotic effects. May cause damage to organs by inhalation.
<b>Skin contact</b>	Causes skin irritation.  2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.
<b>Eye contact</b>	Causes serious eye irritation.

**Symptoms related to the physical, chemical and toxicological characteristics** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritant effects.

### Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways. Narcotic effects.

Product	Species	Test Results
15 OZ TERAND GRAFFITI RMVR PLSTC-SAFE (CAS Mixture)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Guinea pig	76874.5 mg/kg, 24 Hours estimated 5772.0059 ml/kg, 24 Hours estimated 183.1984 ml/kg, 4 Days estimated 49.6894 ml/kg, 2 Days estimated
	Rabbit	3363.8601 mg/kg, 24 Hours estimated 42.7367 ml/kg, 24 Hours estimated
	Rat	16638.1309 mg/kg estimated
<i>Inhalation</i>		
LC100	Cat	461.5266 % estimated
LC50	Mouse	26880.4785 ppm, 6 Hours estimated 22326.9551 ppm, 8 Hours estimated 6343.4272 mg/l, 120 Minutes estimated 4470.939 mg/l, 2 Hours estimated 266.6598 %, 120 Minutes estimated 82.0492 mm/l, 2 Hours estimated
	Rabbit	10038.2705 ppm, 7 Hours estimated
	Rat	24672.9648 ppm, 6 Hours estimated 9659.6055 ppm, 4 Hours estimated 476.7194 mg/l, 6 Hours estimated 52.46 mg/l, 4 Hours estimated 27.2807 mg/l/4h estimated
<i>Oral</i>		
LD100	Rabbit	14837.4482 mg/kg estimated

Product	Species	Test Results
LD50	Dog	17441.4961 mg/kg estimated
	Guinea pig	17313.0645 mg/kg estimated
	Mouse	57415.8281 mg/kg estimated
	Rabbit	62111.8008 mg/kg estimated
	Rat	6786.7261 mg/kg estimated
		22.7746 ml/kg estimated
Components	Species	Test Results
2-Butoxyethanol (CAS 111-76-2)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Guinea pig	230 ml/kg, 24 Hours
		7.3 ml/kg, 4 Days
	Rabbit	450 ml/kg, 24 Hours
		435 mg/kg, 24 Hours
		220 mg/kg
		0.63 ml/kg
	Rat	> 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rabbit	400 ppm, 7 Hours
	Rat	450 ppm, 4 Hours
		2.21 mg/l/4h
<i>Oral</i>		
LD100	Rabbit	695 mg/kg
LD50	Dog	> 695 mg/kg
	Guinea pig	1200 mg/kg
	Rat	530 - 2800 mg/kg
		470 mg/kg
Acetone (CAS 67-64-1)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
		50.1 mg/l
<i>Oral</i>		
LD50	Rat	5800 mg/kg
		2.2 ml/kg
Butane (CAS 106-97-8)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l

Components	Species	Test Results
Diethylene Glycol Monobutyl Ether (CAS 112-34-5)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Guinea pig	2 ml/kg, 2 Days
	Rabbit	2764 mg/kg, 24 Hours
<i>Oral</i>		
LD100	Rabbit	4000 mg/kg
LD50	Guinea pig	2000 mg/kg
	Mouse	2410 mg/kg
	Rabbit	2500 - 3000 mg/kg
	Rat	3306 mg/kg
Propane (CAS 74-98-6)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
Sodium Hydroxide (CAS 1310-73-2)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rat	1350 mg/kg
Toluene (CAS 108-88-3)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Mouse	6405 - 7436 ppm, 6 Hours
		5320 ppm, 8 Hours
	Rat	5879 - 6281 ppm, 6 Hours
		12.5 - 28.8 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	5000 mg/kg

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Causes skin irritation.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not available.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
2-Butoxyethanol (CAS 111-76-2)	3 Not classifiable as to carcinogenicity to humans.
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>	
Not listed.	
<b>Reproductive toxicity</b>	May damage fertility or the unborn child.



<b>Specific target organ toxicity - single exposure</b>	Narcotic effects.
<b>Specific target organ toxicity - repeated exposure</b>	Respiratory system. Skin. Kidneys. Central nervous system. Eyes. Liver. May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.
<b>Chronic effects</b>	Prolonged inhalation may be harmful. May be harmful if absorbed through skin.  2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.  May cause damage to organs through prolonged or repeated exposure.

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Product		Species	Test Results
<b>15 OZ TERAND GRAFFITI RMVR PLSTC-SAFE (CAS Mixture)</b>			
<b>Aquatic</b>			
Algae	IC50	Algae	1799.8043 mg/L, 72 Hours estimated
Crustacea	EC50	Daphnia	31.8818 mg/l, 48 hours estimated
Fish	LC50	Fish	101.2207 mg/L, 96 Hours estimated
<b>Components</b>			
<b>Species</b>			
<b>Test Results</b>			
2-Butoxyethanol (CAS 111-76-2)			
<b>Aquatic</b>			
Crustacea	EC50	Daphnia	1819 mg/L, 48 Hours
Fish	LC50	Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours
9-Octadecenoic Acid (CAS 112-80-1)			
<b>Aquatic</b>			
Fish	LC50	Fathead minnow (Pimephales promelas)	205 mg/l, 96 hours
Acetone (CAS 67-64-1)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Diethylene Glycol Monobutyl Ether (CAS 112-34-5)			
<b>Aquatic</b>			
Fish	LC50	Bluegill (Lepomis macrochirus)	1300 mg/l, 96 hours
Sodium Hydroxide (CAS 1310-73-2)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	34.59 - 47.13 mg/l, 48 hours
Fish	LC50	Fish	45, 96 Hours
Toluene (CAS 108-88-3)			
<b>Aquatic</b>			
Algae	IC50	Algae	433.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	7.645 mg/L, 48 Hours
		Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

**Partition coefficient n-octanol / water (log Kow)**

2-Butoxyethanol 0.83

**Partition coefficient n-octanol / water (log Kow)**

Acetone	-0.24
Butane	2.89
Diethylene Glycol Monobutyl Ether	0.56
Propane	2.36
Toluene	2.73

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

**13. Disposal considerations**

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**US RCRA Hazardous Waste U List: Reference**

Acetone (CAS 67-64-1)	U002
Toluene (CAS 108-88-3)	U220

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

**14. Transport information****DOT**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	None
<b>Packing group</b>	Not applicable.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	N82
<b>Packaging exceptions</b>	306
<b>Packaging non bulk</b>	None
<b>Packaging bulk</b>	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

**IATA**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	Yes
<b>ERG Code</b>	10L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

**Other information**

**Passenger and cargo aircraft** Allowed.

**Cargo aircraft only** Allowed.

**Packaging Exceptions** LTD QTY

**IMDG**

**UN number** UN1950

**UN proper shipping name** AEROSOLS

**Transport hazard class(es)**

**Class** 2.1

**Subsidiary risk** -

**Label(s)** 2.1

**Packing group** Not applicable.

**Environmental hazards**

**Marine pollutant** Yes

**EmS** F-D, S-U

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

**Packaging Exceptions** LTD QTY

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

**DOT**



**IATA; IMDG**



**Marine pollutant**



**General information**

IMDG Regulated Marine Pollutant.

**15. Regulatory information**

**US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Acetone (CAS 67-64-1)	Listed.
Sodium Hydroxide (CAS 1310-73-2)	Listed.
Toluene (CAS 108-88-3)	Listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

<b>Hazard categories</b>	Immediate Hazard - Yes
	Delayed Hazard - Yes
	Fire Hazard - Yes
	Pressure Hazard - No
	Reactivity Hazard - No

**SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** No**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Toluene	108-88-3	20 - 40

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Toluene (CAS 108-88-3)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

**Safe Drinking Water Act (SDWA)** Not regulated.**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

Acetone (CAS 67-64-1)	6532
Toluene (CAS 108-88-3)	6594

**Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**

Acetone (CAS 67-64-1)	35 %WV
Toluene (CAS 108-88-3)	35 %WV

**DEA Exempt Chemical Mixtures Code Number**

Acetone (CAS 67-64-1)	6532
Toluene (CAS 108-88-3)	594

**US state regulations****US. Massachusetts RTK - Substance List**

2-Butoxyethanol (CAS 111-76-2)  
 Acetone (CAS 67-64-1)  
 Butane (CAS 106-97-8)  
 Propane (CAS 74-98-6)  
 Sodium Hydroxide (CAS 1310-73-2)  
 Toluene (CAS 108-88-3)

**US. New Jersey Worker and Community Right-to-Know Act**

2-Butoxyethanol (CAS 111-76-2)  
 Acetone (CAS 67-64-1)  
 Butane (CAS 106-97-8)  
 Propane (CAS 74-98-6)  
 Sodium Hydroxide (CAS 1310-73-2)  
 Toluene (CAS 108-88-3)

**US. Pennsylvania Worker and Community Right-to-Know Law**

2-Butoxyethanol (CAS 111-76-2)  
 9-Octadecenoic Acid (CAS 112-80-1)

Acetone (CAS 67-64-1)  
Butane (CAS 106-97-8)  
Propane (CAS 74-98-6)  
Sodium Hydroxide (CAS 1310-73-2)  
Toluene (CAS 108-88-3)

#### US. Rhode Island RTK

Acetone (CAS 67-64-1)  
Butane (CAS 106-97-8)  
Propane (CAS 74-98-6)  
Sodium Hydroxide (CAS 1310-73-2)  
Toluene (CAS 108-88-3)

#### US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

##### US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3) Listed: January 1, 1991

##### US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3) Listed: August 7, 2009

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date 08-11-2014

Version # 01

#### Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

#### Revision Information

Product and Company Identification: Product Codes  
Composition / Information on Ingredients: Ingredients  
Physical & Chemical Properties: Multiple Properties  
Transport Information: Material Transportation Information  
Transport information: General information  
Regulatory Information: United States  
GHS: Classification