

# Safety Data Sheet

## 1. Identification

<b>Product Information:</b>	EZ-P
<b>Product Name:</b>	EasyCare Acrylic Latex Eggshell Finish Pure White (Pastel Base)
<b>Recommended Use:</b>	Non-Flat Latex Paint
<b>Application Method:</b>	No Information
<b>Supplied by:</b>	True Value Manufacturing 201 Jandus Road Cary, IL 60013 Telephone: (847) 639-5383
<b>Emergency Telephone:</b>	(866)257-3981

## 2. Hazards Identification

**EMERGENCY OVERVIEW:** Under normal use conditions, this product is not expected to cause adverse health effects. This product does contain a material which can cause cancer. Crystalline silica has been classified by IARC and NTP as a carcinogen for humans (Group 1) from lab animal studies. Risk of cancer depends on duration and level of exposure from sanding surfaces or spray mist. When sanding or spraying product use (NIOSH/MSHA approved) respiratory protection.

### GHS Classification

Carc. 1A

### Symbol(s) of Product



### Signal Word

Danger

### Possible Hazards

4% of the mixture consists of ingredients of unknown acute toxicity

### GHS HAZARD STATEMENTS

Carcinogenicity, category 1A	H350	May cause cancer. Classified as carcinogenic Category 1 on the basis of epidemiological and/or animal data. Mixtures are classified as carcinogenic when at least 1 ingredient has been classified as carcinogenic and is present at 0.1% or above. Routes of exposure are dependant on ingredient form.
------------------------------	------	--

### GHS LABEL PRECAUTIONARY STATEMENTS

P201	Obtain special instructions before use.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313	IF exposed or concerned: Get medical advice/attention.

## 3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
TITANIUM DIOXIDE	13463-67-7	10-25	GHS07	H312
DIATOMACEOUS EARTH	61790-53-2	1.0-2.5	No Information	No Information
ALUMINA (ALUMINUM OXIDE)	1344-28-1	1.0-2.5	GHS07	H332
MICA	12001-26-2	1.0-2.5	No Information	No Information

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFF	64742-54-7	0.1-1.0	GHS08	H350
HYDRATED ALUMINUM MAGNESIUM SILICATE	12174-11-7	0.1-1.0	No Information	No Information
DIPHENYL KETONE	119-61-9	0.1-1.0	GHS08	H373
CRYSTALLINE SILICA	14808-60-7	0.1-1.0	GHS08	H350
FELDSPAR	68476-25-5	<0.1	No Information	No Information

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

#### 4. First-aid Measures



**FIRST AID - INHALATION:** Remove person to fresh air. If signs/symptoms continue, get medical attention.

**FIRST AID - SKIN CONTACT:** WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND CLEAN BEFORE REUSE.

**FIRST AID - EYE CONTACT:** FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL HELP IF IRRITATION PERSISTS.

**FIRST AID - INGESTION:** Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Have the victim drink 8 to 10 ounces (240 - 300 ml) of water to dilute the material in the stomach. If vomiting occurs naturally, have the victim lean forward to reduce the risk of aspiration. Consult a physician immediately.

#### 5. Fire-fighting Measures

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Container may rupture on heating.

**SPECIAL FIREFIGHTING PROCEDURES:** Use a self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

**EXTINGUISHING MEDIA:** Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

#### 6. Accidental Release Measures

**ENVIRONMENTAL PRECAUTIONS:** No Information

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** ISOLATE HAZARD AREA AND KEEP UNNECESSARY PEOPLE AWAY. DO NOT ALLOW THE LIQUID TO ENTER INTO ANY SEWERS, ONTO THE GROUND OR INTO ANY BODY OF WATER. FOR LARGE SPILLS, USE A DIKE AND PUMP INTO APPROPRIATE CONTAINERS. SMALL SPILLS, DILUTE WITH WATER AND RECOVER OR USE NON-COMBUSTIBLE ABSORBENT MATERIAL AND SHOVEL INTO WASTE CONTAINERS.

#### 7. Handling and Storage



**HANDLING:** KEEP FROM FREEZING

**STORAGE:** Store in a cool dry area. KEEP OUT OF REACH OF CHILDREN.

#### 8. Exposure Controls/Personal Protection

##### Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
TITANIUM DIOXIDE	10 mg/m3	N.E.	15 mg/m3 (Total dust)	N.E.
DIATOMACEOUS EARTH	10 mg/m3	N.E.	80 mg/m3	N.E.
ALUMINA (ALUMINUM OXIDE)	1 mg/m3 Respirable Dust	N.E.	5 mg/m3 Respirable Dust	N.E.
MICA	3 mg/m3	N.E.	3 mg/m3	N.E.
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFF	5 mg/m3	10 mg/m3	5 mg/m3	N.E.
HYDRATED ALUMINUM MAGNESIUM SILICATE	N.E.	N.E.	N.E.	N.E.

DIPHENYL KETONE	N.E.	N.E.	0.5 mg/m3	N.E.
CRYSTALLINE SILICA	0.05 mg/m3 Respirable Dust	N.E.	0.1 mg/m3 Respirable Dust	N.E.
FELDSPAR	2 mg/m3 (Respirable dust)	N.E.	5 mg/m3 (Respirable dust)	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation  
Sk = Skin Sensitizer N.E. = Not Established

### Personal Protection



**RESPIRATORY PROTECTION:** In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.



**SKIN PROTECTION:** Sensitive individuals should wear gloves to prevent repeated contact.



**EYE PROTECTION:** Safety glasses with side-shields



**OTHER PROTECTIVE EQUIPMENT:** No Information



**HYGIENIC PRACTICES:** Wash hands before eating, drinking, or smoking.

## 9. Physical and Chemical Properties

<b>Appearance:</b>	Thick Liquid	<b>Physical State:</b>	Liquid
<b>Odor:</b>	Slight Ammonia	<b>Odor Threshold:</b>	No Information
<b>Density, g/cm3:</b>	0.000	<b>pH:</b>	No Information
<b>Freeze Point, °C:</b>	No Information	<b>Viscosity:</b>	No Information
<b>Solubility in Water:</b>	No Information	<b>Partition Coefficient, n-octanol/ water:</b>	No Information
<b>Decomposition temperature, °C</b>	No Information		
<b>Boiling Range, °C:</b>	98 - 104	<b>Explosive Limits, %:</b>	N/A
<b>Combustibility:</b>	Does not Support Combustion	<b>Flash Point, °C:</b>	Not Applicable
<b>Evaporation Rate:</b>	No Information	<b>Auto-Ignition Temperature, °C</b>	No Information
<b>Vapor Density:</b>	No Information	<b>Vapor Pressure, mmHg:</b>	No Information

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

**STABILITY:** THIS MATERIAL IS STABLE UNDER NORMAL STORAGE AND HANDLING CONDITIONS.

**CONDITIONS TO AVOID:** AVOID HIGH TEMPERATURES AND FREEZING.

**INCOMPATIBILITY:** No Information

**HAZARDOUS DECOMPOSITION PRODUCTS:** MAY GENERATE TOXIC OR IRRITATING COMBUSTION PRODUCTS. MAY GENERATE CARBON MONOXIDE GAS.

## 11. Toxicological Information



### Practical Experiences

**EFFECT OF OVEREXPOSURE - INHALATION:** Vapors or spray mists may be irritating to eyes, nose or throat. Prolonged overexposure may cause coughing, shortness of breath, dizziness, and intoxication. This product contains crystalline silica, which is considered a hazard by inhalation.

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATION.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** MILD EYE IRRITANT.

**EFFECT OF OVEREXPOSURE - INGESTION:** May be harmful if swallowed. May cause gastrointestinal disturbance.

**EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS:** Crystalline silica is known to cause silicosis, a noncancerous lung disease. Exposure is by route of inhalation. If material is in a liquid matrix it is unlikely to be inhaled.

**CARCINOGENICITY:** Crystalline silica has been classified by IARC and NTP as a carcinogen for humans (Group 1) from lab animal studies. Inhalation of crystalline silica can cause cancer. Risk of cancer depends on duration and level of exposure from sanding surfaces or spray mist. When sanding or spraying product use (NIOSH/MSHA approved) respiratory protection. IARC lists Titanium Dioxide and Diphenyl Ketone as possible human carcinogens (Group 2B)

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Contact

### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
13463-67-7	TITANIUM DIOXIDE	10000 mg/kg	2000 mg/kg	N.I.
1344-28-1	ALUMINA (ALUMINUM OXIDE)	>10000 mg/kg	N.I.	N.I.

N.I. = No Information

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** No Information

## 13. Disposal Information



### Product

**DISPOSAL METHOD:** DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. ALL DISPOSAL METHODS MUST BE IN COMPLIANCE WITH ALL FEDERAL, STATE/PROVINCIAL, AND LOCAL LAWS AND REGULATIONS.

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** ISOLATE HAZARD AREA AND KEEP UNNECESSARY PEOPLE AWAY. DO NOT ALLOW THE LIQUID TO ENTER INTO ANY SEWERS, ONTO THE GROUND OR INTO ANY BODY OF WATER. FOR LARGE SPILLS, USE A DIKE AND PUMP INTO APPROPRIATE CONTAINERS. SMALL SPILLS, DILUTE WITH WATER AND RECOVER OR USE NON-COMBUSTIBLE ABSORBENT MATERIAL AND SHOVEL INTO WASTE CONTAINERS.

## 14. Transport Information

**SPECIAL TRANSPORT PRECAUTIONS:** No Information

**DOT Proper Shipping Name:** No Information  
**DOT Technical Name:** No Information  
**DOT Hazard Class:** No Information  
**DOT UN/NA Number:** No Information

**Packing Group:** No Information  
**Hazard SubClass:** No Information  
**Resp. Guide Page:** No Information

## 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Health Hazard, Chronic Health Hazard

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
AMMONIUM HYDROXIDE	1336-21-6
IODOPROPYNYL BUTYLCARBAMATE	55406-53-6
FORMALDEHYDE	50-00-0

#### TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

### U.S. State Regulations:

#### NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
WATER	7732-18-5
ACRYLIC POLYMER	Proprietary
Nepheline Syenite	37244-96-5

#### PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
WATER	7732-18-5
ACRYLIC POLYMER	Proprietary
Nepheline Syenite	37244-96-5

#### CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

<u>Chemical Name</u>	<u>CAS-No.</u>
TITANIUM DIOXIDE	13463-67-7
HYDRATED ALUMINUM MAGNESIUM SILICATE	12174-11-7
DIPHENYL KETONE	119-61-9
CRYSTALLINE SILICA	14808-60-7
FORMALDEHYDE	50-00-0
ETHYLENE OXIDE	75-21-8

#### CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

<u>Chemical Name</u>	<u>CAS-No.</u>
ETHYLENE OXIDE	75-21-8

