

## Safety Data Sheet

according to the third revision of the GHS

Date of issue: 07/30/2014

Version: 1.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product Form : Mixture

Trade name : John Deere Cool-Gard™ II Premix
Product code : TY26575, TY26576, TY26577, TY26578

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine Coolant and anti-freeze

## 1.3. Details of the supplier of the safety data sheet

#### MANUFACTURER:

Northland Products 1000 Rainbow Drive Waterloo, IA 50704

Tel: +1-319-234-5585 +1-800-772-1724

### SUPPLIER:

Deere & Company One John Deere Place Moline, IL 61265

E-mail: ESOC@JohnDeere.com

### 1.4. Emergency telephone number

Emergency number

: Chemtrec 1-800-424-9300

Chemtrec (Outside USA) +1 703-527-3887 (24 hours) Supplier: +1-309-748-5636 or 1-800-822-8262 (24 hours)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

GHS classification

Acute Tox. 4 (Oral) H302 Skin Irrit. 2 H315 Eye Irrit. 2A H319 STOT RE 2 H373

### 2.2. Label elements

**GHS** labelling

Hazard pictograms (GHS)





GHS07

GHS08

Signal word (GHS) : Warning

Hazard statements (GHS) : H302 - Harmful if swallowed H315 - Causes skin irritation

H319 - Causes serious eye irritation

H373 - May cause damage to organs (kidneys) through prolonged or repeated exposure (oral)

Precautionary statements (GHS) : P260 - Do not breathe dust/fume/gas/mist/vapours/spray

P264 - Wash hands thoroughly after handling

P280 - Wear protective clothing/eve protection/face protection

P302+P352 - IF ON SKIN! Wash with plenty of water

P305+F351+P338 - IF N EYES: Rinse cautiously withwater for several minutes. Remove

contactlenses, if present and easy to do. Contirue rinsing P312 - Cali a POISON CENTER/doctor if you feel unwell P314 - Get medical advice/attention if you feel unwell

P321 - Specific treatment (see on this label)
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: get medical advice/attention

P362 - Take off contaminated clothing

P501 - Dispose of contents/container to comply with applicable local, national and international

regulation.

08/01/2014 EN (English) SDS Ref.: 81Q2 Page 1

other hazards which do not result in classification

: Spills of this product present a serious slipping hazard.

#### 2.4. Unknown acute toxicity (GHS)

No data available

### SECTION 3: Composition/information on ingredients

### Substance

Not applicable

Full text of H-phrases: see section 16

4.12	

Name	Product identifier	%	
Ethylene glycol	(CAS No.) 107-21-1 (EC no) 203-473-3 (EC index no) 603-027-00-1	45 - 50	
Sodium tetraborate decahydrate	(CAS No.) 1303-96-4 (EC no) 215-540-4 (EC index no) 005-011-01-1	0.5 – 1.5	
Sodium hydroxide	(CAS No.) 1310-73-2 (EC no) 215-185-5 (EC index no) 011-002-00-6	0.5 ~ 1.5	

### SECTION 4: First aid measures

### Description of first aid measures

First-aid measures general

- : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice
  - (show the label where possible).

First-aid measures after inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Assure fresh air breathing. If breathing is difficult, give oxygen. In all cases of doubt, or when symptoms persist, seek medical advice.

First-aid measures after skin contact

- Rinse and then wash skin thoroughly with water and soap. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

First-aid measures after eye contact

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. If redness, burning, blurred vision or swelling occur, transport to nearest medical facility for additional treatment. Get medical advice/attention.

First-aid measures after ingestion

: If swallowed, rinse mouth with water (only if the person is conscious). Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Obtain emergency medical attention.

## Most important symptoms and effects, both acute and delayed

Symptoms/injuries

: Causes damage to organs (kidneys) (Oral).

Symptoms/injuries after inhalation

: Long-term (repeated). Inhalation of mist or aerosol may cause irritation to nose and throat.

Symptoms/injuries after skin contact

: Causes skin imitation.

Symptoms/injuries after eye contact

: Causes serious eye irritation. Swelling and inflammation.

Symptoms/injuries after ingestion

: Harmful if swallowed. Ingestion may cause nausea and vomiting. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. In the case of extreme exposure there is a risk of severe metabolic acidosis and haemorrhagy. Death in extreme cases.

Symptoms may be delayed.

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. Symptoms may be delayed.

## SECTION 5: Firefighting measures

## Extinguishing media

Suitable extinguishing media : Do not use a water jet since it may cause the fire to spread. Unsuitable extinguishing media

: Foam, Dry powder, Carbon dioxide, Water fog, Water spray, Sand.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard

: When heated above the flash point, releases vapours. Gas/vapours, flammable.

Explosion hazard

Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

## Advice for firefighters

Precautionary measures fire

: Stop and contain spill/release if it can be done safely. If this cannot be done, allow fire to burn under control. Gases/vapours, toxic.

SDS Ref.: 81Q2 2/0 08/01/2014 EN (English)

## Safety Data Sheet

according to the third revision of the GHS

: Exercise caution when fighting any chemical fire. Do not use direct water stream; may spread Firefighting instructions fire. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Heat may build pressure, rupturing closed containers, spreading fire and

increasing risk of burns and injuries. Cool closed containers exposed to fire with water spray. Prevent fire-fighting water from entering environment.

Protective equipment for firefighters : Wear approved self-contained breathing apparatus (set on positive pressure mode). Do not enter

fire area without proper protective equipment, including respiratory protection.

Other information Special danger of slipping by leaking/spilling product. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).

### SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures

General measures : Spilled material may present a slipping hazard. Stop leak if safe to do so. Eliminate all ignition

sources if safe to do so.

For non-emergency personnel 6.1.1.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

**Emergency procedures** : Ensure adequate ventilation, especially in confined areas.

### Environmental precautions

Prevent contamination of soil, drains and surface waters. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### Methods and material for containment and cleaning up

Methods for cleaning up

: Approach from upwind. For small spills, absorb or cover with dry earth, sand, or other inert noncombustible absorbent material and place into waste containers for later disposal. Gather the product and place it in a spare container that has been suitably labelled. Consult the appropriate authorities about waste disposal. Large spills: Contain large spills to maximize product recovery or disposal. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Shovel into suitable and closed container for disposal. Minimize generation of dust. Store away from other materials. Ensure all national/local regulations are

### Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

### Precautions for safe handling

Additional hazards when processed

: Special danger of slipping by leaking/spilling product.

Precautions for safe handling

Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray. Provide good ventilation in process area to prevent formation of vapour. Personal protective equipment should be selected based upon the conditions under which this product is handled or used. Empty container retains product residue. Use and store away from all naked flames, heat sources or working electrical appliances. Do not smoke.

Hygiene measures

Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Discard contaminated leather articles. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### Conditions for safe storage, including any incompatibilities

Technical measures

: Provide adequate ventilation. A washing facility/water for eye and skin cleaning purposes should

Storage conditions

Keep out of reach of children. Keep container tightly closed. Keep only in the original container in a cool, well-ventilated place away from highly flammable substances. Keep away from open flames, hot surfaces and sources of ignition. Keep out of direct sunlight. Protect from moisture. Containers that have been opened must be carefully resealed and kept upright to prevent

Incompatible materials

Refer to Section 10 on Incompatible Materials.

Heat and ignition sources

Remove all sources of ignition.

Storage area

: Store in dry, cool, well-ventilated area. Keep away from heat and direct sunlight.

## Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

## Control parameters

08/01/2014 EN (English) SDS Ref.: 81Q2

# Safety Data Sheet according to the third revision of the GHS

Ethylene glycol (107-21-	1)	
USA ACGIH	ACGIH Ceiling (mg/m³)	100 mg/m³
Argentina	OEL - Ceiling TWA (CMP-C)	100 mg/m³ (inhalable fraction)
Chile	OEL - Ceiling (LPA's) (ppm)	40 ppm (aerosol)
Chile	OEL - Ceiling (LPA's) (mg/m³)	100 mg/m³ (aerosol)
Colombia	OEL - Ceiling (mg/m³)	100 mg/m³ (aerosol)
Dominican Republic	OEL - Ceiling (mg/m³)	100 mg/m³ (aerosol)
Mexico	OEL - Ceiling (LMPE-Pico) (mg/m³)	100 mg/m³ (aerosol)
Nicaragua	OEL - Ceiling (mg/m³)	100 mg/m³ (aerosol only)
Peru	OEL - Ceiling (ppm)	39 ppm
Peru	OEL - Ceiling (mg/m³)	100 mg/m³
Peru	OEL- Skin Designations	Skin – potential significant contribution to overall exposure by cutaneous route
Uruguay	OEL - Ceiling (mg/m³)	100 mg/m³ (aerosol)
Venezuela	OEL - Ceiling (mg/m³)	100 mg/m³
Venezuela	OEL- Skin Designations	Skin – potential significant contribution to overall exposure by cutaneous route

Sodium tetraborate deca	shydrate (1303-96-4)	
USA ACGIH	ACGIH TWA (mg/m³)	2 mg/m³
USA ACGIH	ACGIH STEL (mg/m³)	6 mg/m³
Argentina	OEL – Ceiling TWA (CMP)	5 mg/m³
Colombia	OEL – STEL (mg/m³)	6 (mg/m³) (inhalable fraction, listed under Borate compounds, inorganic)
Colombia	OEL – TWA (mg/m³)	2 mg/m³ (inhalable fraction, listed under Borate compounds, inorganic)
Dominican Republic	OEL – STEL (mg/m³)	6 (mg/m³) (inhalable fraction, listed under Borate compounds, inorganic)
Dominican Republic	OEL – TWA (mg/m³)	2 mg/m³ (inhalable fraction, listed under Borate compounds, inorganic)
Mexico	OEL – TWA (LMPE-PPT) (mg/m³)	5 mg/m³ (aerosol)
Nicaragua	OEL – STEL (mg/m³)	6 (mg/m³) (inhalable fraction, listed under Borate compounds, inorganic)
Nicaragua	OEL – TWA (mg/m³)	2 mg/m³ (inhalable fraction, listed under Borate compounds, inorganic)
Peru	OEL – TWA (mg/m³)	5 mg/m³
Uruguay	OEL – STEL (mg/m³)	6 (mg/m³) (inhalable fraction, listed under Borate compounds, inorganic)
Uruguay	OEL – TWA (mg/m³)	2 mg/m³ (irihalable fraction, listed under Borate compounds, inorganic)
Venezuela	OEL – TWA (CAP) (mg/m³)	5 mg/m³

Spalming property of the Seal		
USA ACGIH	ACGIH Ceiling (mg/m³)	2 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	2 mg/m³
Argentina	OEL - Ceiling (CMP-C)	2 mg/m³
Chile	OEL Ceiling (LPA's) (mg/m*)	2 mg/m³
Colombia	OEL - Ceiling (mg/m³)	2 mg/m³
Dominican Republic	OEL - Ceiling (mg/m³)	2 mg/m³
Mexico	OEL - Ceiling (LMPE-Pico) (mg/m³)	2 mg/m³
Nicaragua	OEL - Ceiling (mg/m³)	2 mg/m³
Peru	OEL - Ceiling (mg/m³)	2 mg/m³
Uruguay	OEL - Ceiling (mg/m³)	2 mg/m³
Venezuela	OEL - Ceiling (mg/m³)	2 mg/m³

08/01/2014 EN (English) SDS Ref.: 81Q2 4/9

## Safety Data Sheet

according to the third revision of the GHS

Appropriate engineering controls

: A washing facility/water for eye and skin cleaning purposes should be present. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of mists and/or vapors below the recommended exposure limits. Ensure adequate ventilation.

Personal protective equipment

: Avoid all unnecessary exposure. Personal protective equipment should be selected based upon the conditions under which this product is handled or used. For certain operations, additional Personal Protection Equipment (PPE) may be required. Gloves. Protective clothing. Protective goggles.







Hand protection

: Wear protective gloves. Nitrile-rubber protective gloves. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Eye protection

Chemical goggles or safety glasses. with side-shields. Eye protection, including both chemical splash goggles and face shield, must be worn when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection

: Chemical resistant suit. Wear rubber boots. Wear suitable protective clothing.

Respiratory protection

Other information

Vapour pressure

: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Use a properly fitted, air-purifying or air-fed respirator if neceassary.

: Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

## Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear viscous liquid.

Colour Gold. Odour Odourless. Odour threshold : 25 ppm pΗ : 7.8 - 8.5 Relative evaporation rate (butyl acetate=1) : 0.01

Melting point : -13 °C (9 °F) Freezing point : -37 °C (-34 °F) **Boiling** point : 129 °C (264 °F) Flash point : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Flammability (solid, gas) : No data available

Relative vapour density at 20 °C : 2.1

Relative density : 1.07 - 1.08 g/cm<sup>3</sup>

Solubility : Water: completely soluble

Soluble in: Water. Diethyl ether. Methanol

: < 0.008 kPa

Log Pow : -1.07

Log Kow : No data available Viscosity, kinematic : No data available Viscosity, dynamic Explosive properties : No data available : No data available

Oxidising properties Explosive limits : No data available

### 9.2. Other Information

**VOC** content : 49.5

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

No additional information available

08/01/2014 SDS Ref.: 81Q2 EN (English)

## Safety Data Sheet

according to the third revision of the GHS

### Chemical stability

Stable at normal conditions.

### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

No additional information available

### Incompatible materials

Oxidizing agents. Strong acids. Strong bases. Contact with Aluminium, Zinc and Tin can cause formation of hydrogen that together with air can be an combustible mixture.

### Hazardous decomposition products

unburned hydrocarbons. Fume. Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

## Information on toxicological effects

John Deere Cool-Gard™ II Premix

LD50 dermal rabbit

ATE CLP (oral)

: Harmful if swallowed. Acute toxicity

ATE CLP (oral)	500.000 mg/kg bodyweight	
Ethylene glycol (107-21-1)		
LD50 oral rat	4000 mg/kg	

Sodium tetraborate decahydrate (1303-96-4)		
LD50 oral rat	2660 mg/kg	

	•
Bearing green till after til 13	
LD50 dermal rabbit	1350 mg/kg
ATE CLP (dermal)	1350.000 mg/kg bodyweight

Skin corrosion/irritation : Causes skin irritation.

pH: 7.8 - 8.5

9530 µl/kg

500.000 mg/kg

: Causes serious eye irritation. Serious eye damage/irritation

pH: 7.8 - 8.5

: Not classified (Based on available data, the classification criteria are not met) Respiratory or skin sensitisation Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met) Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

Reproductive toxicity : Not classified (Conclusive but not sufficient for classification)

: Not classified (Based on available data, the classification criteria are not met) Specific target organ toxicity (single exposure)

Specific target organ toxicity (repeated

exposure)

: May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).

Potential Adverse human health effects and

symptoms

: Not classified (Based on available data, the classification criteria are not met)

: Based on available data, the classification criteria are not met.

Symptoms/injuries after inhalation

Aspiration hazard

: Long-term (repeated). Inhalation of mist or aerosol may cause irritation to nose and throat.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation. Swelling and inflammation.

: Harmful if swallowed. Ingestion may cause nausea and vomiting. Depression of the central Symptoms/injuries after ingestion

nervous system, headaches, dizziness, drowsiness, loss of coordination. In the case of extreme exposure there is a risk of severe metabolic acidosis and haemorrhagy. Death in extreme cases.

Symptoms may be delayed.

### SECTION 12: Ecological information

## 12.1. Toxicity

Ethylene glycol (107-21-1)	
LC50 fishes 1 41000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)	
EC50 Dapinia 1	46300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	14 - 18 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])

6/O 08/01/2014 EN (English) SDS Ref.: 81Q2

## Safety Data Sheet

according to the third revision of the GHS

Sodium hydroxide (1310-73-2)	
LC50 fishes 1	45.4 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
12.2. Persistence and degradability	
John Deere Cool-Gard™ II Premix	
Persistence and degradability	Not established.
12.3. Bioaccumulative potential	
The property of the Contents of	
Log Pow	-1.07
Bioaccumulative potential	Not established.
Mydic deposition and	
Log Pow	-1.93

## 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispos

: Dispose of contents/container to comply with applicable local, national and international regulations. Liquid product may not be disposed of with household waste or landfilled. Do not allow to enter into drains/waters or in the soil. Do not re-use empty containers. Since emptied containers retain product residue, follow label warnings even after container is emptied. Dispose in a safe manner in accordance with local/national regulations. Dispose of at an licensed site.

Additional information

: Do not pressunze, cut, weld, braze, solder, drill, grind, or expose containers to flames, sparks,

heat, or other potential ignition sources. Empty container retains product residue.

Ecology - waste materials

: Prevent contamination of soil, drains and surface waters. Avoid release to the environment.

## **SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

## 14.1. UN number

Not applicable

## 14.2. UN proper shipping name

Not applicable

### 14.3. Additional Information

Other information : RQ values - Refer to section 15

Overland transport

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

## SECTION 15: Regulatory information

## 15.1. US Federal regulations

John Deere Cool-Gard™ II Premix		
RQ (Reportable quantity, section 304 of EPA's List of Lists):	10526 lb	

Ethylene glycol (107-21-1)		
Listed on the United States TSCA (Toxic Substa Listed on United States SARA Section 313	nces Control Act) inventory	
EPA TSCA Regulatory Flag	Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.	
RQ (Reportable quantity, section 304 of EPA's List of Lists):	5000 lb	
SARA Section 313 - Emission Reporting	1.0 %	

08/01/2014 EN (English) SDS Ref.: 81Q2 7/6

## Safety Data Sheet

according to the third revision of the GHS

Sodium	tetraborate	decah	wirate	(1303-96-4)
Oodidiii	totiabolate	decan	yurate	1202-20-4

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### Sodium hydroxide (1310-73-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

RQ (Reportable quantity, section 304 of EPA's

List of Lists):

## 15.2, International regulations

#### CANADA

John Deere Cool-Gard™ II Premix	
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Ethylene glycol (107-21-1)	
Listed on the Canadian DSL (Dome	stic Sustances List)
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Sodium tetraborate decahydrate (1303-96-4)	odium tetraborate decahydrate (1303-96-4)	
Listed on the Canadian DSL (Domestic Sustance	s List)	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	

Listed on the Canadian DSL (Domestic Sustance	s List)
WHMIS Classification	Class E - Corrosive Material

### **EU-Regulations**

### Ethylene glycol (107-21-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

## Sodium hydroxide (1310-73-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

Classification according to Directive 67/548/EEC or 1999/45/EC

No additional information available

## 15.2.2. National regulations

### Ethylene glycol (107-21-1)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Canadian IDL (Ingredient Disclosure List)

## Sodium tetraborate decahydrate (1303-96-4)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Pollutant Release and Transfer Register Law (PRTR Law) Listed on the Canadian IDL (Ingredient Disclosure List)

08/01/2014 EN (English) SDS Ref.: 81Q2 8/9

## Safety Data Sheet

according to the third revision of the GHS

### Sodium hydroxide (1310-73-2)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Poisonous and Deleterious Substances Control Law

Listed on the Canadian IDL (Ingredient Disclosure List)

## 15.3. US State regulations

No additional information available

## SECTION 16: Other information

Other information

: None.

Full text of H-phrases: see section 16:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
H302	Harmful if swallowed
H315	Causes skin irritation
H319	Causes serious eye irritation
H373	May cause damage to organs through prolonged or repeated exposure

SDS (third revision of the GHS)

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Northland Products Company's knowledge; however, Northland Products Company makes no warranty whatsoever, expressed or implied, of merchantability or fitness for the particular purpose, regarding the accuracy of such data or the results to be obtained from the use thereof. Northland Products Company assumes no responsibility for the injury to the recipient or to third party persons or for any damage to any property and recipient assumes all such

SDS Ref.: 81Q2 08/01/2014 EN (English)