MSDS - Material Safety Data Sheet

Product Name: LIQUID WRENCH PENETRATING OIL

MSDS No.: L106

I. Basic Information:

Manufacturer: RADIATOR SPECIALTY COMPANY
Address: 600 RADIATOR ROAD
City, ST Zip: INDIAN TRAIL, NC 28079
Country:

Contact: Robert Geer
Information Telephone Number: 704-684-1811
Emergency Contact: Rocky Mountain Poision Control Center
Emergency Telephone Number: 303-623-5716
Emergency Restrictions:

Product Name: LIQUID WRENCH PENETRATING OIL
MSDS No.: L106

Issue Date: 02/19/2008
Supersedes Date: 10/12/2006

II. Hazards Identification:

EMERGENCY OVERVIEW

Danger: Flammable. Harmful or fatal if swallowed. Eye and skin irritant. Contents under pressure.

Level 3 Aerosol

OSHA Regulatory Status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Potential Health Effects

Route(s) of Entry:

Absorption, Inhalation, and Ingestion.

Health Hazards (Acute and Chronic):

N/D

Signs and Symptoms:

Eye Contact: Irritant. Prolonged contact may cause conjunctivitis.
Skin Contact: Irritant. Defatting of tissue, dermatitis may occur.
Inhalation: Irritant to mucous membranes. Repeated exposure may cause narcosis, dizziness, respiratory or lung irritation.
Ingestion: HARMFUL OR FATAL IF SWALLOWED. May cause burns to mouth, throat & stomach.

Medical Conditions Generally Aggravated by Exposure:

N/D

Other Health Warnings:

Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia and pulmonary edema which is a potentially fatal condition.

Potential Environmental Effects

Not Available

III. Composition/Information on Ingredients:

Chemical Name	CAS No.	% Range	Trade Secret
Carbon dioxide	124-38-9	1.0 - 5.0	
Fragrance	Proprietary	0.1 - 1.0	
Kerosene	8008-20-6	40.0 - 70.0	
Naphthenic Petroleum Distillate	64742-52-5	15.0 - 40.0	
Solvent-Refined Heavy Paraffinic	64741-88-4	0.1 - 1.0	

IV. First Aid Measures:

Emergency and First Aid Procedures:

MSDS - Material Safety Data Sheet

Product Name: LIQUID WRENCH PENETRATING OIL

MSDS No.: L106

Eye Contact: Flush eyes with clean water for 15 minutes while lifting eyelids. Get prompt medical attention.
Skin Contact: Wash with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Launder contaminated clothing before reuse.
Inhalation: Remove to fresh air. If breathing becomes difficult give oxygen and get prompt medical attention. If breathing stops, give artificial respiration and get prompt medical attention.
Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately. Aspiration of vomitus into the lungs can cause pneumonitis, which can be fatal.

Note to Physicians:

N/E

V. Fire Fighting Measures:

Suitable Extinguishing Media:

Water Fog, Foam, Carbon Dioxide, Dry Chemical

Unsuitable Extinguishing Media:

Do not use forced water stream as this could cause the fire to spread.

Products of Combustion:

Normal products of combustion, smoke, carbon dioxide, carbon monoxide, and sulfur trioxides.

Protection of Firefighters:

Wear self-contained positive pressure breathing apparatus and protective clothes. Use shield to protect from rupturing and venting containers. At elevated temperatures containers may vent, rupture or burst, even violently

VI. Accidental Release Measures:

Personal Precautions:

Eliminate all ignition sources. Persons not wearing protective equipment should be excluded from area of spill until clean up has been completed.

Environmental Precautions:

Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occurred. Run off to sewer may create fire or explosion hazard.

Methods for Containment:

Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc).

Methods for Cleanup:

Using a non-metalic scoop, place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material.

Other Information:

All equipment used with handling the concentrate must be grounded. If run-off occurs, notify proper authorities as required that a spill has occurred.

VII. Handling and Storage:

Handling Precautions:

Use with adequate ventilation and proper protective equipment.
Do not use or store near fire, sparks, or open flame. Do not puncture or incinerate container. Exposure to sunlight and temperatures above 120° may cause container to vent, rupture, or burst.

Storage Precautions:

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS! Danger: Flammable.

VIII. Exposure Controls/Personal Protection:

MSDS - Material Safety Data Sheet
Product Name: LIQUID WRENCH PENETRATING OIL
MSDS No.: L106

Chemical Name	OSHA PEL	ACGIH TLV	Other Limits
Kerosene	N/AV	100 ppm	Not Available
Naphthenic Petroleum Distillate	5 mg/m3	5 mg/m3	Not Available
Solvent-Refined Heavy Paraffinic	5 mg/m3	5 mg/m3	Not Available
Fragrance	N/D	N/D	Not Available
Carbon dioxide	N/AV	5000 ppm	Not Available

Engineering Controls:

Use with adequate ventilation. If TLV is exceeded, wear NIOSH approved respirator.

Personal Protective Equipment:

See Section 2 for applicable exposure limits. For prolonged exposure wear protective safety glasses, gloves, and apron.

IX. Physical and Chemical Properties:

Boiling Point: 320 F
Boiling Range: Not Available
Solubility In Water: Insoluble
Flash Point: 132F
Odor Threshold: Not Available
Vapor Density (AIR = 1): N/A
pH Range: Not Available
Decomposition Temp: Not Available
Lower Explosive Limit: 0.7%
Specific Gravity (H20 = 1): 0.85
Other Information: VOC Content: 36.938

Melting Point: N/A
Freezing Point: Not Available
Evaporation Rate (Butyl Acetate = 1): N/A
Flash Point Method: TCC
Appearance and Odor: Dark Liquid with petroleum odor
Vapor Pressure (mm Hg.): N/A
Partition Coefficient: Not Available
Auto-Ignition Temp: Not Available
Upper Explosive Limit: 5%

X. Stability and Reactivity:

Stability:

Product is stable

Conditions to Avoid:

See Incompatible Materials below

Incompatible Materials:

Avoid contact with strong oxidizers

Hazardous Decomposition Products:

Normal products of combustion, smoke, carbon dioxide, carbon monoxide, and sulfur trioxides.

Possibility of Hazardous Reactions:

Will not occur

XI. Toxicological Information:

N/D

XII. Ecological Information:

N/D

MSDS - Material Safety Data Sheet

Product Name: LIQUID WRENCH PENETRATING OIL

MSDS No.: L106

XIII. Disposal Considerations:

DISPOSAL: This container may be recycled in aerosol recycling centers when empty. Before offering for recycling, empty the can by using the product according to the label. DO NOT PUNCTURE! If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with all local, state government and federal laws and regulations.

XIV. Transport Information:

Shipping Name: Not Available

DOT Hazard Class: Not Available

UN/NA#: Not Available

DOT Subsidiary Hazard Class: Not Available

Packing Group: Not Available

Transportation Information:

DOT Hazard Class: ORM-D
Shipping Name: Consumer Commodity

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for international and air shipping purposes.

ICAO/IATA (US)
Shipping Name: Aerosols
Class: 2.1
UN number: UN1950

International:

ICAO/IATA
UN number: UN1950
Shipping Name: Aerosols
Class: 2.1

IMDG
UN number: UN1950
Shipping Name: Aerosols
Class: 2
EmS: F-D, S-U

XV. Regulatory Information:

See Section 2 for SARA Reportable Chemicals.

USA TSCA: All components of this material are listed on the US TSCA Inventory.

Warning: This product contains a chemical(s) known to the State of California to cause cancer or birth defects or other reproductive harm.

XVI. Other Information:

Chemical State: [X] Liquid [ ] Gas [ ] Solid

Chemical Type: [ ] Pure [X] Mixture

Hazard Category:

[X] Acute [ ] Chronic [X] Fire

[X] Pressure [ ] Reactive

Additional Manufacturer Warnings:

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS!



C Pers. Protection

N/E: Not Established
N/D: Not Determined
N/A: Not Applicable
N/AV: Not Available

MSDS - Material Safety Data Sheet
Product Name: LIQUID WRENCH PENETRATING OIL

MSDS No.: L106

Additional Product Information:

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for information, investigation, and verification. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.